WATER LEAK ALARM
ALARM DE DÉTECTION DE FUITE D'EAU

EASY TO INSTALL:

The detector is powered by 2 AA batteries (not included).

Do not mix old and new batteries. Do not mix rechargeable and alkaline batteries.

1. Open the battery cover on the detector and install the batteries.
2. Replace the cover and press firmly to ensure a snug fit.
3. Insert the sensing cable into the cable sensor jack on the bottom of the detector.
4. Place detector so the cable is positioned where leaks are most likely to occur.
5. The detector can be placed flat on the floor or mounted on a surface. For wall mounting, use double-sided tape (included) to adhere to a dry surface.

FACILE À INSTALLER:

Le détecteur est alimenté par 2 piles AA (non incluses).

Ne mélangez pas des piles neuves avec des vieilles piles. Ne mélangez pas des piles alcalines avec des piles rechargeables.

1. Ouvrez le couvercle de pile sur le détecteur et installez les piles.
2. Replacez le couvercle et appuyez fermement pour assurer l'étanchéité.
3. Insérez le câble de détection dans la prise au-dessous du détecteur.
4. Placez le détecteur afin que le câble soit situé là où les fuites sont plus susceptibles de survenir.
5. Le détecteur peut être placé à plat sur le sol ou fixé sur un mur. Pour montage mural, utilisez un ruban double-face (incluse) et collez sur une surface sèche.