

Instructions

To remove safety tab

1. Firmly hold the head of the nozzle and trigger in place.
2. Pull tab forward on top of nozzle until it snaps off.

To check for intermittent faults

3. Spray directly on component using bursts of spray.
4. Use extension tube to direct the spray in hard to reach corners.

NOTE: Avoid touching

Packaging and Supporting Products

<i>Cat. No.</i>	<i>Packaging</i>	<i>Net Volume</i>		<i>Net Weight</i>		<i>Packaging Weight</i>	
403A-285G	Aerosol	236 mL	7.98 fl oz	285 g	10 oz	4.1 kg ^{a)}	9 lb
403A-400G	Aerosol	332 mL	11.2 fl oz	400 g	14.1 oz	5.0 kg ^{a)}	11 lb

a) Pack of 10

Technical Support

Contact us regarding any questions, improvement suggestions, or problems with this product. Application
www.mgchemicals.com.

support@mgchemicals.com

Phone: +(1) 800-340-0772 (Canada, Mexico & USA)
+(1) 905-331-1396 (International)
Fax: +(1) 905-331-2862 or +(1) 800-340-0773

Mailing address: **Manufacturing & Support**
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Head Office
9347-193rd Street
Surrey, British Columbia, Canada
V4N 4E7