

Technical Specifications	
Amperage (A)	9
Compatible Tip Size (in)	0.009, 0.011, 0.013, 0.015
Engine Size (HP)	0.5
Fluid Outlet Size (in)	0.25
Fluid Outlet Thread Type	NPSM
Frame Configuration	Stand
Includes	SG2 Spray Gun, TrueAirless 515 Spray Tip, Spray Tip Guard, 1/4 in x 25 ft DuraFlex Hose, Pump Armor Storage Fluid (8 oz), Quick Start-Up Guide
Inlet Paint Strainer	35 Mesh Stainless Steel Screen
Maximum Flow Rate (GPM)	0.27
Maximum Hose Length (ft)	75
Maximum Tip Size (in)	0.015
Maximum Tip Size 1 Gun (in)	0.015
Maximum Working Pressure (MPa)	20.7
Maximum Working Pressure (psi)	3000
Minimum Generator Power (W)	2500
Model	Magnum
Motor Type	Universal
Number of Guns	1
Overall Height (in)	17.9
Overall Length (in)	14.5
Overall Width (in)	12.4
Phase	1
Power Rating (HP)	0.5
Power Rating (W)	373
Power Rating (kW)	0.37
Power Source	Electric
Pressure Control Type	Adjustable
Product Series	Project
Pump Rod Type	Hardened Stainless Steel
Pump Sleeve Material	Stainless Steel
Recommended Annual Usage (gal)	125
Series	X5
Type	Airless Sprayer
Voltage (V)	120
Weight (lb)	17
Wetted Material	Aluminum, Brass, Carbide, Fluroelastomer, Leather, Nylon, PVC, Plated Steel, Polypropylene, Stainless Steel, UHMWPE