



国光电子

MATERIAL SAFETY DATA SHEET

Apower Electronics Co., Ltd

MSDS No: 100826

Product Name:Lithium-ion Polymer Rechargeable Cell

Form No. :D-50-155 Rev. :3.5 Issued and Revised Date:January 12th 2010

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name:Lithium-ion Polymer Rechargeable Cell

Applicable Models/Sizes: AEC423448

Supplier Identification:

Apower Electronics Co., Ltd, For Short "AEC"

Block F1, guo guang Industrial Park, hua du borough, Guang zhou City, China

TEL:86-20-28609182 FAX:86-20-28609173

Contact Point:

Apower Electronics Co., Ltd

Block F1, guo guang Industrial Park, hua du borough, Guang zhou City, China

TEL:86-20-28609182 FAX:86-20-28609173

[Http://www.aecbattery.com](http://www.aecbattery.com) e-mail:sales@aecbattery.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Information about the chemical nature of product:

Ingredient Name	CAS NO. :	Concentration
Energy Value	...	2.516 Wh/pcs
Equivalent Max Lithium Content	...	0.204 g/pcs
Lithium Cobalt Dioxide	12190-79-3	47.46%
Aluminum foil	7429-90-5	6.12%
Graphite(various Carbons)	7782-42-5	19.54%
Copper foil	7440-50-8	8.63%
Organic electrolyte	Keep secret	14.47%
Lithium hexafluorophosphate	21324-40-3	3.79%
Inert components	...	balance

3. Independent Certification of Lithium-ion cell UN Transportation Model Regulation(UN38.3)

No	Test Item	Criteria	Result	Remark
T1	Altitude Simulation	No mass loss, leakage, venting, disassembly, rupture, and fire. OCV should not be less than 90% before testing.	Passed	
T2	Thermal Test	No mass loss, leakage, venting, disassembly, rupture, and fire. OCV should not be less than 90% before testing.	Passed	
T3	Vibration	No mass loss, leakage, venting, disassembly, rupture, and fire. OCV should not be less than 90% before testing.	Passed	
T4	Shock	No mass loss, leakage, venting, disassembly, rupture, and fire. OCV should not be less than 90% before testing.	Passed	
T5	External Short Circuit	External temperature should not exceed 170 degC. No disassembly, rupture, and fire within six hours of this test.	Passed	
T6	Impact	External temperature should not exceed 170 degC. No disassembly, rupture, and fire within six hours of this test.	Passed	
T7	Overcharge	No disassembly, and fire within seven days of this test.	Passed	Battery only
T8	Forced Discharge	No disassembly, and fire within seven days of this test.	Passed	

We confirmed the test results based on the UN manual of tests and criteria(UN38.3).

4. HAZARDS IDENTIFICATION

Safety Performance

There is no physical danger of ignition or chemical danger of hazardous materials' leakage during normal use.

As the cell with Laminated Aluminum Foil outer package is different from the tradition metal-shelled case liquid lithium cell, it can reduce safety problems arising and it can't detonate even exposed to a fire.

Potential Health Effects:

Cobalt and Cobalt compounds are considered to be possible human carcinogen(s). These chemicals may cause allergic skin sensitization(rash) and irritate eyes, skin, nose, throat, respiratory system.

Since electrolyte is flammable liquid, it does not bring close to fire. It may cause moderate to severe eye irritation, dryness of the skin. Breathing of its mist, vapor or fume may irritate nose, throat and lungs. Exposure of electrolyte material in the area which contains water may generate hydrofluoric acid, which can cause immediate burns on skin, severe eye burn. The ingestion of electrolyte can cause serious chemical burn of mouth, esophagus and gastrointestinal tract.

5. FIRST-AID MEASURES

◆Eyes: Flush with water for at least 15 minutes. If irritation occurs and persists, contact a medical doctor.

◆Skin: Remove contaminated clothing and thoroughly wash with soap and plenty of water. If irritation persists, contact a medical doctor.

◆Inhalation: Remove to fresh air. If breathing difficulty or discomfort occurs and persists, see a medical doctor. If breathing has stopped, give artificial respiration and see a medical doctor IMMEDIATELY.

6. FIRE-FIGHTING MEASURE

◆Hazardous Combustion Products: When burned, hazardous products of combustion including fumes of carbon monoxide, carbon dioxide, and fluorine can occur

◆Extinguishing Media: Water, carbon dioxide, dry chemical, or foam.

◆Basic Fire Fighting Procedures: Wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

◆Unusual Fire Hazards: This material does not represent an unusual fire hazard.

7. ACCIDENTAL RELEASE MEASURES

◆Procedure for Release and Spill: Sweep up and place in a suitable container, dispose or waste according to all local, state and Federal Laws and Regulations.

◆Before cleanup measures begin, review the entire MSDS with particular attention Potential Health Effects; and on Recommended Personal Protective Equipment.

8. HANDLING AND STORAGE

◆Handling

Specific safe handling advice: Never throw out cells in a fire or expose to high temperatures. Do not soak cells in water and seawater. Do not expose to strong oxidizers.

Do not give a strong mechanical shock or throw down. Never disassemble, modify or deform. Do not connect the positive terminal to the negative terminal with electrically conductive material.

◆Storage conditions (suitable, to be avoided): Do not place the battery cell near heating equipment, nor expose to direct sunlight for long periods. Elevated temperatures can result in shortened battery cell life and degrade performance.

Store in cool place (temperature: -20~45°C, humidity: 45~85%).

Incompatible products: Conductive materials, water, seawater, strong oxidizers and strong acids

Packing material (recommended, not suitable): Insulative and tearproof materials are recommended.

9. EXPOSURE CONTROLS/PERSONAL PROTECTION

- ◆Engineering controls: Investigate engineering techniques to reduce exposures use with adequate ventilation and recommended personal protective equipment.
- ◆Eye/Face protection: Use good industrial practice to avoid eye contact. Processing of this product releases vapors or fumes which may cause eye irritation. Where eye contact may be likely wear chemical goggles and have eye flushing equipment available
- ◆Skin protection: Minimize skin contamination by following good industrial hygiene practices. Wearing protective gloves is recommended. Wash hands and contaminated skin thoroughly after handling.
- ◆Respiratory protection: Avoid breathing dust and processing vapors. When adequate ventilation is not available, wear a NIOSH/MSHA respirator approved for protection against inorganic dusts.
- ◆Special clothing: Robber gloves.

10. PHYSICAL PROPERTIES

Physical state: Solid
Form: Geometric solid
Color: Metallic color (without outer pack cover)
Odor: No odor
Ph: Not Applicable
Flash point: Not Applicable
Explosion properties: Not Explosible
Density: Not Applicable
Solubility: Not Soluble

11. STABILITY AND REACTIVITY

Hazardous reactions may occur under some specific conditions.

- ◆Conditions to avoid: When a battery cell is exposed to an external short-circuit, crushes, modification, high temperature above 100°C, it will be the cause of heat generation and ignition. Avoid to be exposed to direct sunlight and high humidity.
- ◆Materials to avoid: Conductive materials, water, seawater, strong oxidizers and strong acids.
- ◆Hazardous decomposition products: Acrid or harmful gas is emitted during fire.

12. TOXICOLOGICAL INFORMATION

Eco Toxicological Information: No information available.

Local Environmental Effects: Unknown.

Since some internal materials remain in the environment, do not bury or throw out into the environment.

13. DISPOSAL INFORMATION

Waste disposal must be in accordance with the applicable regulations. Disposal of the lithium ion battery cells should be performed by permitted, professional disposal firms knowledgeable in State or Local requirements of hazardous waste treatment and hazardous waste transportation. Incineration should never be performed by battery but users, eventually by trained professional in authorized facility with proper gas and fume treatment.

14. TRANSPORTATION/SHIPPING AND REGULATORY INFORMATION

◆US DOT, All AEC batteries are not subject to the requirements of the Department of Transportation(DOT) subchapter C, Hazardous Material Regulations since each AEC battery meets the exceptions under 173.185(b). The AEC batteries are exempted from the US DOT regulations as they are separated to prevent short circuits and packed in strong packing for conditions normally encountered in transportation.

◆ICAO and IATA, The International Civil Aviation Organization(ICAO) and the International Air Transport Association(IATA) fully regulated all Lithium batteries. AEC batteries shipment contains no Item Listed Under IATA DGR Special Provision A154 and it meets all the requirements of the IATA DGR 51st Edition including the passing of the "UN38.3 test" and "1.2m drop test". And AEC batteries can be shipped as "Not Restricted" cargo in accordance with IATA Dangerous Goods Regulations Section II of Packing Instruction 965~967 of IATA DGR Items UN3480 and UN3481.

◆IMO, all AEC batteries are regulated as Hazardous Material by the International Maritime Organization(IMO) when transporting more than 24 batteries or 12 batteries in a single package. These must be transported according to the requirement in Special Provisions "188" and "230".

◆ADR, RID, all AEC batteries are regulated as Hazardous Material by the ADR (road) and RID (rail) when transporting more than 24 batteries or 12 batteries in a single package. These must be transported according to the requirement in Special Provisions "188" and "230".

◆BUILDING OF NEW BATTERY PACK-if you build any of AEC lithium batteries into battery pack, you must assure that the "NEW BATTERY PACK" are being tested in accordance with the UN Recommendations on the Transportation of Dangerous Goods, Manual of Test and Criteria, Part III, Subsection 38.3 again.

For more information contact:

Deng Ya Xi

Quality Dept Manager

Block F1, guo guang Industrial Park, hua du borough, Guang zhou City, China P.C:510800

TEL:86-20-28609370

FAX:86-20-28609173

Mob:13631481841

URL:www.aecbattery.com