

## Cable Length

ATX Cable	1x 600mm (m)
EPS Cable	2x 750mm (m)
PCIe Cable	2x 750mm, 900mm (m) 4x 750mm (m)
SATA Cable	4x 550mm, 650mm, 750mm (m)
Four-Pin Peripheral Cable	1x 550mm, 650mm 750mm (m) 1x 550mm,650mm (m) (f)
Floppy Adapter	1x 100mm
AC Power	1x 1500mm (m)
Modular Cable Type	Full

## Connector Quantity

24 Pin ATX	1x
EPS (CPU)	2x 8pin (4+4)
PCIe	6x 8pin (6+2), 2x 6pin
SATA	12x
Four-Pin Peripheral	5x
Floppy	1x

## Power Specs

AC Input	100 - 240 VAC, 15A, 50 - 60 Hz
Rail	+3.3V+5V+12V +5Vsb-12V
Max Output	20A 20A 99.9A 2.5A 0.5A 99.9A
	100W 1198.8W 12.5W 6W
Total	1200W @ +50C

## Additional Details

Operating Temperature	0° to 50° C
Japanese Capacitors	100%
ECO Mode	Yes
MTBF	100,000 Hours
Net Weight	9 lbs
Size	85mm (H) x 150mm (W) x 200mm (L)
Approvals	TUV, CB, CE, FCC, RCM, cTUVus, BSMI, WEEE, RoHS Compliance with ErP Lot 6 2013 Requirement
Fan Size / Bearing	140mm Double Ball Bearing