

Reolink-Go-IP-Camera-Specifications

	Model	Reolink Go
Video & Audio	Image Sensor	Starlight CMOS Image Sensor
	Video Resolution	1080p HD at 15 frames/sec
	Video Format	H.264
	Field of View	Fixed lens, 110° diagonal
	Night Vision	Up to 10 m (33 ft)
	Digital Zoom	6x digital zoom
	Audio	High-quality speaker and microphone
PIR Detection & Alerts	PIR Detecting Distance	Adjustable up to 10 m (33 ft)
	PIR Detecting Angle	120° horizontal
	Audio Alert	Customized voice-recordable alerts
	Other Alerts	Instant email alerts and push notifications
3G/4G Bandwidth	Frequency Bands	Europe: LTE FDD: B1/B3/B5/B7/B8/B20 WCDMA: B1/B5/B8
		the United States: LTE FDD: B2/B4/B12 WCDMA: B2/B4/B5
		Australia: LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28 LTE TDD: B40 WCDMA: B1/B2/B5/B8
	Transmission Data	LTE FDD: Max 10Mbps (DL), Max 5Mbps (UL) LTE TDD: Max 8.96Mbps (DL), Max 3.1Mbps (UL) HSPA+: Max 42Mbps (DL), Max 5.76Mbps (UL) UMTS: Max 384Kbps (DL), Max 384Kbps (UL)
Power	Battery	7800mAh rechargeable battery (Battery life varies based on settings, usage & temperature)
	Solar	Can be powered by Reolink Solar Panel
	DC Power	Can be powered by 5V/2A power adaptor
Storage	Local Storage	Supports up to 64GB micro SD card
	SD Card Requirement	Read and Write Speed: Class 10 or higher; Format: FAT32
Working Environment	Operating Temperature	-10° to 55° C (14° to 131° F)
	Weather Resistance	IP65 certified weatherproof
Size & Weight	Size	Φ75 x 113 mm (Φ75 x 4.4 in)
	Weight (Battery included)	380 g (13.4 oz)
Warranty	Limited Warranty	2-year limited warranty.