

Cable Length

ATX Cable	1x 600mm (m)
EPS Cable	1x 700mm, 850mm (m)
PCIE Cable	2x 700mm, 850mm (m)
SATA Cable	3x 500mm, 600mm, 700mm (m)
Four-Pin Peripheral Cable	2x 500mm, 600mm, 700mm (m)
Floppy Adapter	1x 100mm
AC Power	1x 1500mm (m)
Modular Cable Type	Full

Connector Quantity

24 Pin ATX	1x
EPS (CPU)	1x 8pin, 1x 8pin (4+4)
PCIE	2x 8pin (6+2), 2x 6pin
SATA	9x
Four-Pin Peripheral	6x
Floppy	1x

Power Specs

AC Input	100 - 240 VAC, 10A, 50 - 60 Hz				
Rail	+3.3V	+5V	+12V	+5Vsb	-12V
Max Output	24A	22A	54.1A	3.0A	0.5A
			649.2W		
	110W		649.2W	15W	6W
Total	650W @ +50C				

Additional Details

Operating Temperature	0° to 50° C
Japanese Capacitors	100%
ECO Mode	Yes
MTBF	100,000 Hours
Net Weight	6 lbs
Size	85mm (H) x 150mm (W) x 165mm (L)
Approvals	TUV, CB, CE, FCC, RCM, cTUVus, BSMI, CCC, WEEE, RoHS Compliance with ErP Lot 6 2013 Requirement
Fan Size / Bearing	140mm Double Ball Bearing