

## 4. X-T20 Specification

<b>Model name</b>	FUJIFILM X-T20
<b>Number of effective pixels</b>	24.3 million pixels
<b>Image sensor</b>	23.6mm x 15.6mm [APS-C] X-Trans™ CMOS III with primary color filter.
<b>Sensor Cleaning System</b>	Ultra Sonic Vibration
<b>Storage media</b>	SD Card[ - 2GB]/SDHC Card[ - 32GB]/SDXC Card[ - 256GB] UHS-I
<b>Lens Mount</b>	FUJIFILM Xmount
<b>Sensitivity</b>	<b>Standard Output</b>
	AUTO1/AUTO2/AUTO3[up to ISO12800]/ISO200 - 12800 [1/3EV step]
	<b>Extended Output</b>
	ISO100/25600/51200
<b>Viewfinder</b>	0.39-in., approx. 2,360K-dot OLED color viewfinder, Coverage of viewing area vs. capturing area : approx. 100% Eye point : approx. 17.5mm [ from the rear end of the camera's eyepiece], Diopter adjustment : -4m - +2m <sup>-1</sup> [dpt] Magnification : 0.62x with 50mm lens[35mm format equivalent] at infinity and diopter set to -1m <sup>-1</sup> . Diagonal angle of view : approx. 30°[ Horizontal angle of view : approx. 25°] Built-in eye sensor
<b>LCD monitor</b>	3.0-inch, aspect ratio 3:2, approx. 1040K-dot Tilt-type TFT color LCD monitor [approx. 100% coverage]
<b>Movie recording</b>	4K [3840 x 2160] 29.97p / 25p / 24p/23.98P, 100Mbps Continuous recording : up to approx. 10 min. Full HD [1920 x 1080] 59.94p / 50p / 29.97p / 25p / 24p/23.98P, 36Mbps Continuous recording : up to approx. 15 min. HD [1280 x 720] 59.94p / 50p / 29.97p / 25p / 24p/23.98P, 18Mbps Continuous recording : up to approx. 30 min. * For 4K movie recording, use a card with UHS Speed Class 3 or higher. * Although movie recording will continue without interruption when the file size reaches 4 GB, subsequent footage will be recorded to a separate file which must be viewed separately.
<b>Power supply</b>	NP-W126S Li-ion battery [included]
<b>Dimensions / Weight</b>	118.4mm [W] x 82.8mm [H] x 41.4mm [D] / 4.66in. [W] x 3.26in. [H] x 1.63in. [D] [Minimum Depth : 31.9mm / 1.3 in.] Approx. 383g / 13.5 oz. [including battery and memory card] Approx. 333g / 11.8 oz. [excluding accessories, battery and memory card]
<b>Battery life for still images</b>	Approx. 350 frames [When XF35mmF1.4 R is set, LCD monitor ON]
<b>Accessories included</b>	Li-ion battery NP-W126S, Battery charger BC-W126, Body cap, Shoulder strap, Metal strap clip, Protective cover, Clip attaching tool, Owner's manual