Manuel de l’utilisateur - Produit 1:

Rowenta Compact Power XXL Aspirateur Sans Sac, Capacité 2,5L, Pour la Maison, Pour la Voiture, Poils d'Animaux RO4871EA

How to winterize the canopy?

Remove the canopy assembly from the frame pool and use a sponge and clean water to wipe away any soil or stains on the canopy. Store the canopy and accessories in a dry, temperature controlled between 0º – 40ºC (32º – 104ºF) storage location. The original packing can be used for storage.

Why the Pool Canopy clamps are sliding, moving around or will not grip firmly onto the pool horizontal top beams?

The Pool Canopy clamps shall be installed over the pool liner horizontal top sleeves as they provide better gripping surface. Do not install over the frame structure T-joints.

Why my LED pool light with hydroelectric power cannot be lit on or keeps blinking (28691/28692)?

The LED light is powered by the pump water flow that drives the built-in hydroelectric generator, no batteries or external power source is needed. The problem is caused by insufficient pump water flow rate. Follow these steps for troubleshooting. 1) Make sure the LED light is connected to the upper pool return water inlet fitting. 2) Clean any dirt on the light head opening with a garden hose. 3) Clean or replace the filter cartridge/sand media. 4) The required flow rate for 28691 is 450-1,200GPH (1703-4542LPH), for 28692 is 1,200 – 2.500GPH (4542-9463LPH). Make sure your pump flow rate meets the requirement. 5) Check and remove any accessories such as solar mat, sprayer, skimmer and/or vacuum devices from the filtration system circulation line. 6) Make sure all the pump hoses are not twisted or curled up.

Which water return connector should I connect the sprayer to, since there are two water return connectors on my 12'x24'x48" rectangular metal frame pool liner?

Either one works fine. After connecting the sprayer to a water return connector, remember to insert the flow reduction adapter into the strainer on the other water return connector. This will provide a good water flow rate to the sprayer.

Can I use the sprayer with other filter pump brands?

No. We do not recommend the sprayer on filter pumps other than INTEX models. The joints may not fit correctly and the pressure may be too high, causing damage to the product and / or personal injury.

Can we leave the canopy on pool after assembled? What is the maximum wind speed the Pool Canopy can withstand?

Remove canopy and store properly when not in use or in the presence of strong winds, thunderstorms, heavy rain or snow. The canopy will withstand winds up to 19 km/h (12 miles/hour).

Why there is a window on the pool canopy？

Large vented window provides for a cooling airflow, so it makes you feel cooler on hot day.

Does the Pool Canopy provide UV protection?

The Pool Canopy only provides shade, and does not provide UV protection from the sun.

What material the pool canopy is made of?

Polyester fabric.

Can I use the pool with the sprayer on?

No, due to various local, state, national and international standards, the skimmer and sprayer cannot be operated while in the pool since the filter pump is not to be operated when the pool is in use and/or occupied.

Can the canopy fit all the pools?

The canopy only fits round Intex metal frame and Ultra Frame pools from 12 feet to 18 feet (366 cm to 549 cm). Not suitable for pool with “inflatable top ring”.

Which model filter pump or pools are compatible with the sprayer?

The sprayer can be used with all Intex filter pump models (except models M1, M2, 02, 03R, 603, 604, 637 & 638) and with chlorine generator/filter pump (saltwater pool system/filter pump) models 8111/8221/8231. All the Easy Set and Frame pools work with the sprayer as long as the liner has the proper inlet/outlet hose connectors.

What is the minimum flow rate that is functional with the sprayer?

1,000 gal/hr is the minimum flow rate of INTEX filter pumps if the sprayer is to be used effectively.

Does the cover have grommets?

For regular pool cover, it only comes with rope to tighten the cover. For deluxe pool cover, it comes with clips to tighten on the vertical legs.

What is the actual size of my solar cover?

Please refer to the information as attached:

Sizes of Solar Cover
Sizes of Solar Cover

Do INTEX covers have the mesh screen in the middle?

No. Instead of using mesh screen, all the INTEX Above Ground Pool (Easy Set pool and Metal Frame pool) covers are designed with holes in the center and holes around the edges, except for family swim center pool covers.

Does INTEX make Solar Covers?

Yes. We manufacture 8’ (244cm) 10’ (305cm) 12’ (366cm) 15’ (457cm) and 18’ (549cm) for both Easy Set and Round Metal Frame pools. We also distribute 18’X9’ (549cmX274cm) and 24’X12’ (732cmX366cm) for Rectangular Frame Pools.

Do you accept COD (Cash on Delivery) or check? What should I do if I do not have a credit card?

Why is the diameter of my 10'(305cm) solar cover not 10'(305cm)?

A 10’ (305cm) solar cover will FIT a 10’ INTEX metal frame pool or Easy Set pool, it doesn’t mean the diameter of the solar cover is 10’ (305cm), this rule also applies to all sizes of the INTEX solar cover.

Can I pick up the products from your warehouse in Long Beach? (for U.S & Canada only)

No.

Which side of the Intex solar cover should contact with pool water?

The bubble side.

What is the turn-around time on defective (Service Program) claims?

Processing time is approximately 1-2 business days from the date we receive the product. It is then shipped by regular mail or Fed EX Ground from Long Beach CA. Therefore, transit time will be determined by your location.

Is it possible to get a cover for the metal frame pools?

Yes. Covers may be obtained for all metal frame pools. Some frame pool sets come with covers included.

Is a cover included in all the pool sets?

It depends on what package was purchased. Be sure to read the retail box prior to purchasing.

Does INTEX recommend other pool covers to be used with INTEX above ground pools?

No. Always use INTEX debris pool cover with INTEX AGP.

My Solar Cover doesn't fit my easy-set pool. Do I have the wrong size? What should I do?

The diameter of the Solar Cover perfectly matches round metal frame pools, due to the shape of the Easy Set pool; you need to fold the edge of the Solar Cover under the top ring.

Does the color of the printing on the inside of the pool wall fade away with time and does it pose any health risk issue?

Excessive use of pool chemicals can cause the color of the inside wall printing to fade away faster, like a heavy chlorinated public swimming will cause a bathing suit color to fade

Other than Intex Repair Kits (Item# 59632 or part#10114) what kind of glue do you recommend for Intex pools?

A PVC or silicon based glue for repairing camping mats, tents, shoes, inflatable boats, etc are suitable for INTEX pools.

My cover doesn't fit. Do I have the wrong size? What do I do?

Sometimes it is easier to put the cover on with the help of another person. Hold the cover on one end, have another person walk around the pool pulling the cover over the inflatable ring (for Easy Set pools), or down the wall (for frame pools). You can also set the cover under the sun temporarily in order to promote stretching.

What are the benefits of using a Solar Cover?

90% of a swimming pool's heat is lost through the water surface; use of Solar Cover will greatly reduce the heat lost. It will prolong your swimming season.

Which opening should I connect the Hydro Aeration System?

See attached file.

The Position of Hydro Aeration System

Is the INTEX pool cover a "Safety Cover"?

No. The pool covers sold by INTEX are debris covers.

What is the best way to remove algae stains from the pool liner?

Empty the pool, use a soft brush, mild detergent and water to remove algae stains from the pool liner. Thoroughly rinse and dry before refilling or storage.

Can grass grow through the ground cloth and / or pool liner?

Yes, in some cases certain types of hardy grass such as Bermuda or St. Augustine can grow through the liner. Before setting up your pool, it is recommended that you clear the area of these types of hardy grasses. INTEX will not be held responsible for grasses that may grow through the ground cloth and / or pool liner, as this is not a manufacturing defect. A ground cloth or tarp may be helpful in preventing this from occurring.

My pool cover sinks, is it a defective?

No, it's normal, and it will not affect the function of the pool cover.

Winterizing your Above Ground Pool

Your pool can be easily emptied and stored in a safe place during the winter. However, many people choose to leave their pool up year round. In areas where freezing temperatures occur, there is risk of ice damage. It is recommended to drain, disassemble and store the pool in a safe place when temperatures drop below 32 degrees Fahrenheit. See "How To Drain Your Pool" section. Clean pool water thoroughly (If Easy Set Pool make sure the top ring is properly inflated). Remove the skimmer (if applicable) or any accessories attached to the threaded strainer connector. Replace strainer grid if necessary. Be sure all accessories parts are clean and completely dry before storage. Plug the Inlet and Outlet fitting from the inside of the pool with the plug provided (sizes 10' and 12'). Close the Inlet and Outlet Plunger Valve (15', 18', and 24'). Remove the ladder (if applicable) and store in a safe place. Be sure the ladder is completely dry before storage. Remove the hoses that connect the pump and filter to the pool. Add appropriate winter chemicals. Consult your local pool dealer as different regions vary greatly. Cover pool with Intex Pool Cover. IMPORTANT: INTEX POOL COVER IS NOT A SAFETY COVER. Clean and drain pump, filter housing and hoses. Remove and discard old filter cartridge (keep a spare cartridge available for next season). Bring pump and filter parts indoors and store in a safe and dry area, preferably heated. STORING POOL FOR WINTER After draining pool, dry pool liner completely (100%). Sprinkle talcum powder on liner to prevent vinyl from sticking together and to absorb any water you may have missed. Roll pool liner to avoid creases and relocate to storage area. Place it in original carton if you saved it. Keep all small parts together with filter pump, manual, and pool, and then place in an area that will remain at room temperature throughout the storage season.

What are the correct steps to insert the flow reduction adapter into the strainer (for rectangular metal frame pool 12'x24'x48" only)?

Remember to always turn off or unplug the pump before servicing. From inside the pool, unscrew the strainer grid from the threaded strainer connector, insert the flow reduction adapter into the threaded strainer connector, and then screw the strainer grid back on the threaded strainer connector.

My pool has a milky color, do I need to change the water or is it treatable?

Water condition varies from country to country, states, region, and within specific zones and areas. In some regions the water could be "hard water", this is because the water contains excessive minerals, such as calcium and magnesium, thus causing the water to adopt a milky color. Check your local pool supply store for advice on water treatment and balance.

Why are there holes on the solar cover?

The set of small holes on the center of the solar cover are for safety (same concept as the regular pool cover). In addition to that, there are also small holes equally spaced around the perimeter of the solar cover near the edge. Sometimes you may find the holes are not consistent, that'll not affect the efficiency and life of your solar cover.

Why are there holes in the cover? Does INTEX distribute a cover without holes?

For safety reasons there are holes in the top cover. Plus, these small weep holes are also helpful in preventing rain or sprinkler water build up on top of the cover. No, all INTEX pool covers have holes, except for the smaller family swim center pools.

What is the spray range for the Intex sprayer?

The maximum range depends on the flow rate of the filter pump. For 1,000 – 1,500 gal/hr filter pump like Model 12R/22R and Model 635/636, the water can spray up to 9' with proper adjustment of the bypass valve. For 2,000 – 2,500 gal/hr filter pump as Model 51/52 and Model 633/634, the water can spray up to 23' by adjusting the bypass valve. For 3,000-gal/hr filter pump as Model 520R/530R the water can spray up to 24' by adjusting the bypass valve.