

Size & Weight

DIMENSIONS (W X H X D)

Approx. 3 1/4" × 5 1/4" × 5 1/4" (80 mm × 131 mm × 131 mm)

WEIGHT

Approx. 2 lb 1 oz (930 g)

SPEAKER UNIT SIZE

Approx. 0.98" diameter

Display

DISPLAY SYSTEM

SXRD™ three primary colors LCD shutter projection system

DIAGONAL PROJECTION IMAGE SIZE

22" to 80"

DISPLAY RESOLUTION

1366 x 768 pixels

ACCEPTED DIGITAL SIGNALS

480p, 720p, 1080p

LIGHT SOURCE

Laser diode²

DISPLAY TECHNOLOGY

0.37" SXRD™ x1

General

PROJECTION PICTURE SIZE

22" to 80"

General Features

WIRELESS HDMI COMPATIBILITY

IEEE 802.11a/b/g/n (2.4 GHz band, 5 GHz band), MIMO compatible

BUILT-IN STORAGE

Approx. 4 GB ³

PICTURE MODES

JPEG, GIF, PNG, BMP

Hardware

PROJECTION LENS ZOOM / FOCUS

Motor-driven (autofocus) ⁴

Interface

OUTPUT(S)

HDMI IN connector (1), HDMI OUT connector (1 (pass-through)), IR BLASTER connector (Mini jack)

Operating Conditions

OPERATING TEMPERATURE / HUMIDITY

Temperature: 41°F to 95°F (5°C to 35°C) Humidity: 20% to 80% (No condensation, humidity at 41°F (35°C) should be 65% or less)

Power

POWER REQUIREMENT

DC 19.5 V (AC adapter VGP-AC19V77)

BATTERY

Built-in lithium-ion battery

POWER CONSUMPTION (IN OPERATION)

Approx. 18 W, approx. 32 W (charging)

AVAILABLE OPERATING TIME

Approx. 2 hours [s](#)

POWER CONSUMPTION (IN STANDBY)

Approx. 6 W, approx. 20 W (charging)

CHARGING TIME

Approx. 4 hours

Speaker

SPEAKER SYSTEM

2 (monaural) bass reflex system

Video Features

LIGHT OUTPUT

100 lm