

Product Data Sheet

Mobil 1™ Syn Gear Lube LS 75W-90

Mobil Passenger Vehicle Lube, United States

Supreme Performance Synthetic Multi-Purpose Automotive Gear Lubricant

Product Description

Mobil 1™ Syn Gear Lube LS is a supreme performance, synthetic, multi-purpose, SAE 75W-90 automotive gear lubricant designed to help meet the highest level performance requirements of modern passenger vehicles in all types of operating conditions including limited slip applications, as well as, deliver outstanding power transfer performance. Compared to conventional hypoid gear lubricants, Mobil 1 Syn Gear Lube LS 75W-90 performs exceptionally over a wide range of temperatures. Mobil 1 Syn Gear Lube LS 75W-90 achieves this through a unique proprietary formulation, that deliver optimized viscosity-temperature properties together with the highest level of inherent formulation stability and helps to protect against thermal and oxidative degradation, wear and corrosion, viscosity loss associated with premature shearing. It also can be used in extended service and for aiding in fuel economy performance.

Features and Potential Benefits

Mobil 1 Syn Gear Lube LS 75W-90 combines wax-free synthesized hydrocarbon base oils and a specially designed extreme-pressure, limited-slip, sulfur-phosphorous additive system to help provide a significantly higher level of performance in rear axles and differentials versus conventional fluids. Great film strength at higher operating temperatures, reduced fluid friction and low-temperature application down to -50°C helps to provide significant advantages versus conventional mineral oil formulations. It helps to reduce wear and spalling under the high speed, high torque and high horsepower conditions in competitive racing and high performance automobiles. This unique, high technology final drive gear lubricant has demonstrated outstanding performance including fuel economy, extended drain, long-term friction retention, low-temperature capability and improved differential/axle durability and cleanliness. Key features and potential benefits include:

Features

Exceptional thermal stability and resistance to high temperature oxidation

Advantages and Potential Benefits

Helps to extend gear and bearing life due to minimal deposits
Long seal life
Potential extended oil drain/service intervals

| | |
|--|---|
| Outstanding protection against low speed/high torque wear and against high speed scoring | Capability to handle some of the severest driving conditions while delivering smooth efficient and reliable performance |
| Exceptional shear stability | Helps to retain viscosity and film strength under severe operating conditions to prevent wear |
| Excellent rust, staining and corrosion protection of copper and its alloys | Helps to reduce wear Long component life |
| Enhanced frictional properties | Improved fuel economy and reduced operating costs |
| Outstanding low temperature fluidity versus mineral oils | Helps to reduce wear at start up and ease of start up even in arctic conditions |
| Good resistance to foaming | Helps to maintain film strength for reliable lubrication |
| Compatible with typical automotive seals and gaskets | Helps to minimize leakage and reduce contamination |
| Excellent limited-slip performance | Helps to reduce chatter and improve traction |

Applications

- Mobil 1 Syn Gear Lube LS 75W-90 is SUITABLE for use in modern high performance automobiles like SUV's, Vans and Light duty trucks requiring API GL-5 level performance
- Mobil 1 Syn gear Lube LS 75W-90 is intended for initial fill, topping-off or refilling differentials, final drives, transfer cases and other gear applications where lubricants meeting API Service GL-5 and multi-purpose or mild EP gear lubricants are recommended
- Not recommended for automatic, manual or semiautomatic transmissions for which engine oil or automatic transmission fluids are recommended
- Where extended service intervals and warranties are required

Specifications and Approvals

Mobil 1 Syn Gear Lube LS meets or exceeds the requirements of: 75W-90
 API GL-5 X

Typical Properties

Mobil 1 Syn Gear Lube LS

| | |
|-----------------------------------|--------|
| SAE Grade | 75W-90 |
| Viscosity (ASTM D445) | |
| cSt @ 40°C | 103 |
| cst @ 100°C | 14.6 |
| Viscosity Index | 146 |
| Pour Point, °C (ASTM D97) | -39 |
| Flash Point, °C (ASTM D92) | 150 |
| Density@15.6 °C g/ml (ASTM D4052) | 0.859 |

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Mobil , Mobil 1 and the Pegasus design are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.