

Specification

Cable Length

ATX Cable	1x 550mm
EPS Cable	1x 600mm
PCIE Cable	1x 550mm, 670mm
SATA Cable	2x 450mm, 570mm, 690mm
Four-Pin Peripheral Cable	1x 450mm, 570mm, 690mm (f)
Floppy Adapter	1x 120mm
AC Power	1x 1200mm (m)
Modular Cable Type	No

Connector Quantity

24 Pin ATX	1x
EPS (CPU)	1x 8pin (4+4)
PCIE	2x 8pin (6+2)
SATA	6x
Four-Pin Peripheral	3x
Floppy	1x

Input

Input Voltage	100 - 240 VAC
AC Input	8-4A
Input Frequency Range	50 - 60 Hz
Efficiency	80% Typical

Output

Rail	+3.3V+5V+12V +5Vsb-12V
Max output	24A 20A 40A 3A 0.3A 40A
Total	120W 480W15W 3.6W 500W @ +40C

Additional Details

Operating Temperature	0° to 40° C
Japanese Capacitors	No
ECO Mode	No
MTBF	100,000 Hours
Net Weight	3 lbs
Size	85mm (H) x 150mm (W) x 140mm (L)

Approvals

TUV, CB, CE, FCC, RCM, cTUVus, BSMI, CCC, WEEE, RoHS
Compliance with ErP Lot 6 2013 Requirement

Fan Size / Bearing

120mm Sleeve Bearing

UPC

843368026318

EAN

4250812401779