

HARDWARE FEATURES

Plug Type	US
Standards and Protocols	IEEE802.11ac, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b, IEEE 802.11a
Interface	1x 10/100/1000M Ethernet Port (RJ45)
Button	WPS Button, Reset Button, LED Button, Power Button
Power Consumption	12W (max power consumption)
Antenna	4x external
Dimensions (W x D x H)	6.4x 3.4 x 1.6 in. (163 x 86 x 40mm)

WIRELESS FEATURES

Frequency	2.4GHz & 5GHz(11ac)
Signal Rate	5GHz:Up to 1733Mbps 2.4GHz:Up to 800Mbps
Reception Sensitivity	5GHz : 11a 6Mbps:-96dBm@10% PER 11a 54Mbps: -78dBm@10% PER 11ac HT20 mcs8: -69dBm@10% PER 11ac HT40 mcs9: -66dBm@10% PER 11ac HT80 mcs9: -63dBm@10% PER 2.4GHz 11g 54M: -79dBm@10% PER 11n HT20 mcs7: -77dBm@10% PER 11n HT40 mcs7: -74dBm@10% PER
Wireless Modes	Range Extender/Access Point Wireless Statistic Concurrent Mode boost both 2.4G/5G WiFi band High Speed Mode for great speed for HD Gaming and video
Wireless Functions	Access Control LED Control Domain Login Function
Wireless Security	64/128-bit WEP WPA-PSK / WPA2-PSK
Transmission Power	<20dBm(2.4GHz) <23dBm(5GHz)

OTHERS

Certification	FCC, RoHS
Package Contents	AC2600 Wi-Fi Range Extender RE650 Quick Installation Guide
Box Dimensions (W X D X H)	7.9 x 4.9 x 3.8in. (202x 125 x 97mm)
System Requirements	Microsoft® Windows® 98SE, NT, 2000, XP, Vista or Windows 7, 8, 10, Mac® OS, NetWare®, UNIX® or Linux.
Environment	Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing