

## SB8200

# DOCSIS 3.1 Ultra Fast Cable Modem



### FEATURES:

- 2x2 OFDM/ OFDMA DOCSIS<sup>®</sup> 3.1 channels and/or 32x8 SCQAM DOCSIS<sup>®</sup> 3.0
- 1.2 GHz Full Capture Bandwidth Tuner
- Multi Processor Technology with ARM based Application Processor
- Dual Gigabit Ethernet Ports with Auto Negotiate and Auto MDIX
- Switchable upstream filters for 42 MHz or 85MHz operation
- Switchable downstream filters for 85MHz or 108MHz with option for 258MHz and an upper edge of 1218MHz
- US and DS spectrum analyzer
- LEDs indicate DOCSIS 3.0 or DOCSIS 3.1 Operation
- Color coded Rear Panel for ease of installation
- ARRIS Consumer Support via Phone, Email, and Chat
- PNM based network monitoring and diagnosis for Service Provider troubleshooting



### PRODUCT OVERVIEW:

SB8200 supporting DOCSIS 3.1 allows unprecedented data rates to be delivered to Retail consumers. The SB8200 is designed to easily deploy Gigabit+ data services. Switchable US and DS filters are designed to produce superior RF performance while reducing interference in the home network and allowing the flexibility required for the Cable Operators to transition from DOCSIS 3.0 to DOCSIS 3.1. Increased DRAM and Flash allow new applications to be deployed on the modem. This feature-packed unit is intended to serve as the hub of the subscribers network, connecting all IP capable devices (Internet, Data, Voice and Video) throughout the customers premises.

Residential and Small Business High Speed Data Customers often opt to purchase and control their own network devices, avoiding Cable Operator modem lease fees. With the SB8200, consumers can leverage the newest technology and highest data rates offered by their Service Providers. The SB8200 is backward compatible to the highest DOCSIS 3.0 speeds possible, allowing a purchaser to 'future proof' their purchase with the best DOCSIS 3.0 speeds until the Service providers upgrade their network technology to offer DOCSIS 3.1 service.

The SB8200 will help lead the future to advanced home and small office services.

## Interface Speeds

DOCSIS 3.1 Downstream OFDM	10,000 Mbps
DOCSIS 3.1 Upstream	2000 Mbps
GigE	1000 Mbps x 2

## Specifications

### Physical

Operating Temperature °C	0 to 50
Operating Relative Humidity	5-85% (Non condensing)
Storage Temperature °C	-40 to 70
Dimensions (H x W x D) in.	5.24" x 5.24" x 1.65"
Weight lbs	2.1
Diagnostic LED's (Front)	Power, US/DS, Online,
Diagnostic LED's (Rear)	Ethernet Link/Speed

### Interfaces

RF Interface	1 External 'F' type connector
Data Interfaces (bridged)	2 x 10/100/1000 Base-T Ethernet (RJ-45 connector)
Home port	
Input Voltage (nominal)	115VAC, 60 Hz

### RF Downstream

Bonded Channels	Up to 32 SCQAM or 2 OFDM
Tuner Configuration	Full capture tuning range
Configurable Diplex Filter	108MHz-258MHz
Frequency Range (MHz)	108MHz-1218MHz DOCSIS
DOCSIS Data Rate (Mbps Max.)	10 Gbps
RF Input Sensitivity Level (dBmV)	-15 to +15 (DOCSIS)

### RF Upstream

Bonded Channels	Up to 8 SCQAM or 2 OFDMA
Frequency Range (MHz)	5 MHz to 85 MHz
Configurable Diplex Filter	42MHz-85MHz
Data Rate (Mbps Max.)	Over 2 Gbps
RF Output Level (dBmV)	+65 dBmV (64 QAM, single upstream) +57dBmV (64QAM, 4-8 upstreams) +65dBmV (16 QAM, single upstreams)

### Compliance

Certification	Compliant Class B Digital Device – Part 15 of the Federal Communications Commission (FCC), DOCSIS 3.1
Environmental	RoHS, Energy Efficient Ethernet, CeC, Pb-Free, Compliant with SNE Voluntary Environmental Agreement

### Ordering Information

Model	Description	Part Number
SB8200	DOCSIS3.1 Cable Modem	1000205

For information on additional SURFboard products please visit [www.SURFboard.com](http://www.SURFboard.com)

For product support please visit [www.arris.com/consumers](http://www.arris.com/consumers)

**Copyright Statement:** © 2016 ARRIS Enterprises LLC. All rights reserved. No part of this publication may be reproduced in any form or by any means or used to make any derivative work (such as translation, transformation, or adaptation) without written permission from ARRIS Enterprises, LLC ("ARRIS"). ARRIS reserves the right to revise this publication and to make changes in content from time to time without obligation on the part of ARRIS to provide notification of such revision or change. ARRIS, SURFboard and the ARRIS logo are all registered trademarks of ARRIS Enterprises, LLC. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks or the names of their products. ARRIS disclaims proprietary interest in the marks and names of others.

**Note:** The capabilities, system requirements and/or compatibility with third-party products described herein are subject to change without notice.