

Specification

AUMOX

Model: SG528P

Hardware Features

Standards	IEEE802.3,IEEE802.3u,IEEE802.3x,IEEE802.3ab
Interface	26 10/100/1000Mbps RJ45 Ports (Auto Negotiation/Auto MDI/MDIX) Support IEEE 802.3x full duplex and Backpressure half duplex
Indicators	PoE/Data Status,Power
Power	AC: 110-240V~50/60Hz DC: 52V/4.5A(Power Adapter Output)
Dimensions (L × W × H)	440mm×210mm×44mm
Weight	2.45 KG
Switching Capacity	56 Gbps
Mac Address Table	8K
PoE Supply	Port 1 to Port 24 support standard IEEE802.3at/af Power(maximum power for each port is 30W) PoE power type is end-span(1/2+,3/6- line pair)
Power Consumption	In full configuration: <400W Power Supply: ≤400W
POE Transmission Distance	≤100 meters
Transmission Media	10BASE-tx:14880PPS/port 100BASE-tx:148800PPS/port 1000BASE-tx:1488000PPS/port

Software Features

Forwarding Method	Store and Forward
MAC Address Learning	Automatic update
Jumbo Frame	9K

Others

Temperature	Operating Temperature: -10℃~55℃(14℉~131℉) Storage Temperature: -40℃~70℃(-40℉~158℉)
Humidity	Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing
Certification	CE , FCC
Package Contents	28-Port Gigabit Ethernet Switch with 24-Port PoE Power Adapter Quick Installation Guide

AUMOX 28-Port Gigabit Ethernet Switch with 24-Port PoE