

RØDELink Filmmaker Kit Technische Daten

Transmission type	2.4GHz Fixed Frequency Agile System
System dynamic range	112dB
Range (distance)	Up To 100m
Frequency range	35Hz - 22kHz
Maximum output level	1v Rms (2.8v P-p)
Max input signal level	1v Rms (2.8v P-p)
Max latency	4ms

Receiver (RX-CAM)

Power source	2 X AA Battery Or MicroUSB
Antenna	Internal
Output connection	3.5mm TRS Locking Jack Socket - Dual Mono
Output impedance	300Ω
Dimensions	111mm X 65mm X 52mm
Weight	190gm

Transmitter (TX-BELT)

Power source	2 X AA Battery Or MicroUSB
Antenna	Internal
Input connection	3.5mm TRS Locking Jack Socket
Input impedance	10kΩ
Dimensions	111mm X 65mm X 40mm
Weight	190gm

RØDELink LAV

ACOUSTIC & ELECTRICAL SPECIFICATION

Acoustic Principle	Permanently Polarised Condenser
Polar Pattern	Omni-directional

Output Impedance	3k Ω Typical
Frequency Range	20Hz – 20kHz
Maximum SPL	110 dB SPL (@ 1kHz, 1% THD into 1 Ω load)
Sensitivity	-33.5db re 1 Volt/Pascal (21.00mV @ 94 dB SPL) +/- 2dB @ 1kHz
Signal to noise Ratio	67 dB
Equivalent Noise (A-weighted)	27 dB Typical
Dynamic Range	83 dB Typical

MECHANICAL SPECIFICATION

Dimensions 1200.00mmH x 4.50mmW x 4.50mmD

--