

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 11671649 plid Garagenbodenbeschichtung
Print date: 29.10.2024 Revision date: 06.06.2024 EN
Version: 25.0 Issue date: 06.06.2024 Page 1 / 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Article No. (manufacturer/supplier) 11671649
Trade name/designation plid Garagenbodenbeschichtung
RAL 7016, Anthrazitgrau
seidenglänzend

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

coating material water based, recommended use according to technical data sheet
This product is a with biocidal products treated article.

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

plid GmbH
Hebelstr. 10 b Telephone: +49 (0) 76 42-90-7899-0
D-79331 Teningen Telefax: +49 (0) 7642-90-789-299
E-mail Service@plid.online
Homepage: www.plid.online

Information contact:

E-mail (competent person) +49 (0) 172 - 6 22 67 31
t.vanledden@plid.online

1.4. Emergency telephone number

Emergency telephone number +49 4124 606 188

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

Contains the biocidal product CMIT / MIT 3: 1 to maintain storage stability.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms

Hazard statements

not applicable

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.

Hazard components for labelling

not applicable

Supplemental hazard information

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
EUH208 Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
EUH210 Safety data sheet available on request.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description water based acrylic resin

Hazardous ingredients

Classification according to Regulation (EC) No 1272/2008 [CLP]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 11671649
Print date: 29.10.2024
Version: 25.0

plid Garagenbodenbeschichtung
Revision date: 06.06.2024
Issue date: 06.06.2024

EN
Page 2 / 9

EC No. CAS No. Index No.	REACH No. Designation classification: // Remark	weight-%
252-104-2 34590-94-8	01-2119450011-60-XXXX (2-methoxymethylethoxy)propanol Substance with a common (EC) occupational exposure limit value.	2 < 2,5
229-934-9 6846-50-0	01-2119451093-47-0001 1-Isopropyl-2,2-Dimethyltrimethylen diisobutyrat Repr. 2 H361 / Aquatic Chronic 3 H412	2 < 2,5
220-120-9 2634-33-5 613-088-00-6	01-2120761540-60-XXXX 1,2-benzisothiazol-3(2H)-one Acute Tox. 4 H302 / Acute Tox. 2 H330 / Skin Irrit. 2 H315 / Eye Dam. 1 H318 / Skin Sens. 1 H317 / Aquatic Acute 1 H400 / Aquatic Chronic 1 H410 (M = 1) Specific concentration limit (SCL): Skin Sens. 1 H317 >= 0,05	0,01 < 0,015

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.:	11671649	plid Garagenbodenbeschichtung	
Print date:	29.10.2024	Revision date: 06.06.2024	EN
Version:	25.0	Issue date: 06.06.2024	Page 3 / 9

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSIVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

(2-methoxymethylethoxy)propanol
EC No. 252-104-2 / CAS No. 34590-94-8

WEL, TWA: 308 mg/m³; 50 ppm

Remark: (may be absorbed through the skin)

Additional information

TWA : Long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

DNEL:

(2-methoxymethylethoxy)propanol

EC No. 252-104-2 / CAS No. 34590-94-8

DNEL long-term dermal (systemic), Workers: 65 mg/kg

DNEL long-term inhalative (systemic), Workers: 308 mg/m³

DNEL long-term dermal (systemic), Consumer: 15 mg/kg

DNEL long-term inhalative (systemic), Consumer: 37,2 mg/m³

1,2-benzisothiazol-3(2H)-one

Index No. 613-088-00-6 / EC No. 220-120-9 / CAS No. 2634-33-5

DNEL long-term dermal (systemic), Workers: 0,966 mg/kg

DNEL long-term inhalative (systemic), Workers: 6,8 mg/m³

DNEL long-term dermal (systemic), Consumer: 0,345 mg/kg

DNEL long-term inhalative (systemic), Consumer: 1,2 mg/m³

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 11671649 plid Garagenbodenbeschichtung
Print date: 29.10.2024 Revision date: 06.06.2024
Version: 25.0 Issue date: 06.06.2024

EN
Page 4 / 9

PNEC:

(2-methoxymethylethoxy)propanol
EC No. 252-104-2 / CAS No. 34590-94-8
PNEC aquatic, freshwater: 19 mg/L
PNEC sewage treatment plant (STP): 4168 mg/L

1,2-benzisothiazol-3(2H)-one
Index No. 613-088-00-6 / EC No. 220-120-9 / CAS No. 2634-33-5
PNEC aquatic, freshwater: 0,004 mg/L
PNEC aquatic, marine water: 0,0004 mg/L
PNEC aquatic, intermittent release: 0,0011 mg/L
PNEC sediment, freshwater: 0,049 mg/kg
PNEC sediment, marine water: 0,0049 mg/kg
PNEC, soil: 3 mg/kg
PNEC sewage treatment plant (STP): 1,03 mg/L

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used:

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	refer to label
Odour:	characteristic
Odour threshold:	not applicable
Melting point/freezing point:	-75 °C Source: 1-(2-butoxy-1-methylethoxy)propan-2-ol
Initial boiling point and boiling range:	100 °C Method: DIN 53171 Source: Water
Flammability:	not applicable
Lower and upper explosion limit:	
Lower explosion limit:	0,8 Vol-%
Upper explosion limit:	20,4 Vol-% Source: 1-(2-butoxy-1-methylethoxy)propan-2-ol
Flash point:	not applicable

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 11671649 plid Garagenbodenbeschichtung
Print date: 29.10.2024 Revision date: 06.06.2024 EN
Version: 25.0 Issue date: 06.06.2024 Page 5 / 9

Auto-ignition temperature:	194 °C Source: 1-(2-butoxy-1-methylethoxy)propan-2-ol
Decomposition temperature:	not applicable
pH at 20 °C:	not applicable
Cinematic viscosity (40°C):	1249,69 mm²/s
Viscosity at 20 °C:	1500 mPa* s Method: TM 33 b
Solubility(ies):	
Water solubility at 20 °C:	completely miscible
Partition coefficient: n-octanol/water:	see section 12
Vapour pressure at 20 °C:	0,4083 mbar
Density and/or relative density:	
Density at 20 °C:	1,20 g/cm³
Relative vapour density:	not applicable
particle characteristics:	not applicable
9.2. Other information	
Solid content:	51 weight-%
solvent content:	
Organic solvents:	5 weight-%
Water:	43 weight-%

SECTION 10: Stability and reactivity

- 10.1. **Reactivity**
No information available.
- 10.2. **Chemical stability**
Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.
- 10.3. **Possibility of hazardous reactions**
Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.
- 10.4. **Conditions to avoid**
Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.
- 10.5. **Incompatible materials**
not applicable
- 10.6. **Hazardous decomposition products**
Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

(2-methoxymethylethoxy)propanol
oral, LD50, Rat: 5130 mg/kg
dermal, LD50, Rat: 9510 - 14000 mg/kg
inhalative (vapours), LC50, Rat: 3,35 mg/L (7 h)

1-Isopropyl-2,2-Dimethyltrimethylen diisobutyrate
oral, LD50, Rat: 15750 mg/kg
dermal, LD50, Rabbit: > 10000 mg/kg

1,2-benzisothiazol-3(2H)-one
oral, LD50, Rat: 670 - 784 mg/kg
Method: OECD 401
dermal, LD50, Rat: > 2000 mg/kg

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 11671649 plid Garagenbodenbeschichtung
Print date: 29.10.2024 Revision date: 06.06.2024
Version: 25.0 Issue date: 06.06.2024

EN
Page 6 / 9

Method: OECD 402

Skin corrosion/irritation; Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

1,2-benzisothiazol-3(2H)-one

Skin, Guinea pig:

Method: OECD 406

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

1-Isopropyl-2,2-Dimethyltrimethylen diisobutytrat

Germ cell mutagenicity

STOT-single exposure; STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself . The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and has not been classified.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information available on the preparation itself .

Do not allow to enter into surface water or drains.

12.1. Toxicity

(2-methoxymethylethoxy)propanol

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 1919 mg/L (48 h)

Algae toxicity, ErC50: > 0 mg/L (96 h)

Bacteria toxicity, EC10, Pseudomonas putida: 4168 mg/L (18 h)

1-Isopropyl-2,2-Dimethyltrimethylen diisobutytrat

Daphnia toxicity, EC50: 0,146 mg/L (48 h)

Method: OECD 202

Algae toxicity, ErC50: 0,4042 mg/L (72 h)

Method: OECD 201

1,2-benzisothiazol-3(2H)-one

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 1,6 mg/L (96 h)

Daphnia toxicity, EC50, Daphnia magna: 3,27 mg/L (48 h)

Algae toxicity, ErC50, Pseudokirchneriella subcapitata: 0,067 mg/L

Long-term Ecotoxicity

(2-methoxymethylethoxy)propanol

Fish toxicity, LC50, Poecilia reticulata (Guppy): > 1000 mg/L (96 h)

Fish toxicity, NOEC, Daphnia magna (Big water flea): 12 mg/L

1-Isopropyl-2,2-Dimethyltrimethylen diisobutytrat

Fish toxicity, LC50 (96 h)

1,2-benzisothiazol-3(2H)-one

Fish toxicity, NOEC, Oncorhynchus mykiss (Rainbow trout) (28)

12.2. Persistence and degradability

*

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 11671649 plid Garagenbodenbeschichtung
Print date: 29.10.2024 Revision date: 06.06.2024
Version: 25.0 Issue date: 06.06.2024

EN
Page 7 / 9

1,2-benzisothiazol-3(2H)-one
: 0 % ; Evaluation Zahn-Wellens Test
Method: OECD 302B
: > 70 % ; Evaluation Activated Sludge Units
Method: OECD 303A

12.3. Bioaccumulative potential

1-Isopropyl-2,2-Dimethyltrimethylen diisobutyrat
Partition coefficient: n-octanol/water: 4,63
1,2-benzisothiazol-3(2H)-one
Partition coefficient: n-octanol/water: 0,7 ; Evaluation Log KOW
Method: OECD 117
HPLC method

Bioconcentration factor (BCF)

1,2-benzisothiazol-3(2H)-one
Bioconcentration factor (BCF): 6,95
Method: OECD 305

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080112 waste paint and varnish other than those mentioned in 08 01 11

Appropriate disposal / Package Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

No dangerous good in sense of this transport regulation.

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

Land transport (ADR/RID)

not applicable

Marine pollutant

not applicable

14.6. Special precautions for user

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 11671649 plid Garagenbodenbeschichtung
Print date: 29.10.2024 Revision date: 06.06.2024 EN
Version: 25.0 Issue date: 06.06.2024 Page 8 / 9

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

Tunnel restriction code -

Sea transport (IMDG)

EmS-No. not applicable

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L): 66

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC product category: (Cat. A/i) ; VOC limit value: 140 g/l

Maximum VOC content of the product in a ready to use condition (in g/L): 66

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
252-104-2 34590-94-8	(2-methoxymethylethoxy)propanol	01-2119450011-60-XXXX
229-934-9 6846-50-0	1-Isopropyl-2,2-Dimethyltrimethylen diisobutyrat	01-2119451093-47-0001
220-120-9 2634-33-5	1,2-benzisothiazol-3(2H)-one	01-2120761540-60-XXXX

SECTION 16: Other information

Full text of classification in section 3:

Repr. 2 / H361	Reproductive toxicity	Suspected of damaging the unborn child.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.
Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
Acute Tox. 2 / H330	Acute toxicity (inhalative)	Fatal if inhaled.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Aquatic Acute 1 / H400	Hazardous to the aquatic environment	Very toxic to aquatic organisms.
Aquatic Chronic 1 / H410	Hazardous to the aquatic environment	Very toxic to aquatic life with long lasting effects.

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: 11671649 plid Garagenbodenbeschichtung
Print date: 29.10.2024 Revision date: 06.06.2024 EN
Version: 25.0 Issue date: 06.06.2024 Page 9 / 9

EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version