Pilova Splash Guard — Installation & Compatibility Guide

REQUIRED CLEARANCES

- Overall size: 18" W × 5.7" D
- Heights: ribs 1.18"; highest point at silicone collar ~1.5"
- Side clearance (each side of faucet): ≥ 9"
- Faucet back to wall/backsplash: ≥ 1.45"
- Faucet front to sink edge: ≥ 1.6"
- Faucet-hole fit: Ø 1.75"–2.55"
- Recommended faucet handle base height: ≥ 1.25" above deck

NOT COMPATIBLE

- Round or curved sinks
- Side-mounted faucets
- Deck plates / extra-wide faucet bases
- Obstacles within 9" (e.g., built-in soap dispenser/sprayer)
- Very low faucet handles (< 1.25" above deck)

QUICK INSTALL (≈1–2 minutes)

1) Clean and dry the rear sink rim.
2) Center splash guard over the faucet hole; make sure the silicone collar around the hole is not folded and lies flat all around.
3) Engage back clip so the mat lies fully flat against the rear rim.

TROUBLESHOOTING

- Pooling on mat → Re-seat clip and confirm tilt toward sink.
- Won't sit flat → Check for deck plate/obstruction or curved sink edge.
- Handle touches guard → Verify handle base height ≥ 1.25" above deck.



