



Hyper 212 EVO

R2 Revision - Support LGA 2011

Features

- Well-balanced cooling performance provides fin optimizations with perfect balance between high and low speed operations.
- 4 Direct Contact heat pipes with the patented **CDC™** (Continuous Direct Contact) technology - creating a perfect, sleek surface for heat conduction.
- Wide-range PWM fan with unique wave-shaped blade design for excellent airflow.
- Versatile all-in-one mounting solution supporting the latest Intel® LGA 2011 / 1366 / 1155 and AMD FM1 / AM3+.



■ RR-212E-20PK-R2

Compatibility

- All Intel® Socket 2011/1366/1156 / 1155/775 CPU
 - Intel® Core™ i7 Extreme
 - Intel® Core™ i7
 - Intel® Core™ i5
 - Intel® Core™ i3
 - Intel® Core™2 Extreme/Quad/Duo
 - Intel® Pentium®
 - Intel® Celeron®
- All AMD Socket FM1/AM3+ / AM3 AM2+ / AM2 CPU
 - AMD FX-Series
 - AMD A-Series
 - AMD Phenom™ II X4 / X3 / X2
 - AMD Phenom™ X4 / X3
 - AMD Athlon™ II X4 / X3 / X2
 - AMD Athlon™ X2
 - AMD Athlon™
 - AMD Sempron™

(For the latest CPU support information, please visit our website.)

Specifications

CPU Socket	Intel® Socket LGA 2011/1366 / 1156/1155/775 AMD Socket FM1/AM3+ / AM3/AM2+ / AM2
Dimensions	120 x 80 x 159 mm (4.7 x 3.1 x 6.3 inch)
Heat Sink Dimensions	116 x 51 x 159 mm (4.6 x 2.0 x 6.3 inch)
Heat Sink Material	4 Direct Contact Heat Pipes / Aluminum Fins
Heat Sink Weight	465g (1.03 lb)
Fan Dimensions	120x120x25 mm (4.7x4.7x1 inch)
Fan Speed	600 - 2000 RPM (PWM) ± 10%
Fan Air Flow	24.9 - 82.9 CFM ± 10%
Fan Air Pressure	0.3 - 2.7mm H ₂ O ± 10%
Fan Life Expectancy	40,000 hours
Noise Level	9 - 36dBA
Bearing Type	Long Life Sleeve Bearing
Connector	4-Pin
Fan Weight	104g (0.23 lb)
Weight	580g (1.28 lb)



Hyper 212 EVO

R2 Revision - Support LGA 2011

Close Up


Well-Balanced Cooling

Fin optimizations provide perfect balance between high and low speed operations.




4 Direct Contact Heat Pipes

Aluminum fins with 4 direct contact heat pipes to provide excellent heat dissipation.




CDC™ Technology

Patented CDC™ (Continuous Direct Contact) technology - side-by-side heat pipe configurations with no gaps creating a perfectly smooth surface for heat conduction.



All-in-one Mounting Solution

Compatible with Intel® Socket LGA 2011/1366/1156/1155/775 and AMD Socket FM1/AM3+/AM3/AM2+/AM2.



Dual-Fan Design

Supports an optional 2nd 120mm fan to increase cooling performance.



120mm PWM Fan with Quick-snap Fan Bracket Design

Includes a new 120mm PWM fan with anti-vibration rubber pads and a quick-snap cover for an easily expedited fan installation.



Package Information

- EAN Code: 4719512035054
- UPC Code: 884102012921
- Package Dimensions: 157 x 90 x 228 mm
6.2 x 3.5 x 9.0 inch
- Carton Dimensions: 475 x 330 x 255 mm
18.7 x 13.0 x 10.0 inch
- 10pcs per carton
- 48 cartons per pallet

