



Your Wax Attack 2 polisher has been manufactured under stringent quality control. However, if a fault should occur, please send the device, along with an explanation of the problem, to the address below.

Satisfaction guaranteed when used as directed. Manufacturer's liability limited to replacement of product or refund of purchase price upon return of unused portion and proof of purchase. For complete warranty details, please see supplemental **Electrical Safety Warnings and Warranty Statement** insert.

**KEEP OUT OF THE REACH OF CHILDREN.** Do Not Freeze.

Mothers® Polishes•Waxes•Cleaners, Inc.  
 5456 Industrial Drive  
 Huntington Beach, CA 92649-1519  
 Phone: (714) 891-3364  
 Fax: (714) 893-1827

**SAVE THESE INSTRUCTIONS**



**MOTHERS® CALIFORNIA GOLD® CLAY BAR SYSTEM**

Before you wax, it's important to determine if your paint could use the Clay Bar. Paint contamination can be anything from embedded grains of metal, tree sap, or even paint overspray. Feel the surface of your paint with the back of your hand. The surface must feel "glass smooth." If not, you have contamination.

Time for Mothers® California Gold® Clay Bar System. Glide the Clay Bar over the surface with the included lubricant. With almost no effort, the surface will return to a glass smooth finish.

137-900321-120215



# WAX ATTACK II



## INSTRUCTIONS

**IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY TO ENSURE THE SAFE & EFFECTIVE OPERATION OF THE MOTHERS® POWER-PRO POLISHING SYSTEM**

SPECIFICATIONS	
Model	Wax Attack 2
Part No.	40-90032
Input Power	0.65A
Power Supply	110V - 60Hz
Speed	3,600 rpm
Pad Diameter	6.3 inches
Weight	3.52 Lbs



MOTHERS.COM  
 DETAILGUIDE.COM  
 WAXFORUM.COM  
 FACEBOOK.COM/MOTHERSUSA

# BRING BACK YOUR VEHICLE'S SHOWROOM SHINE

Thank you for purchasing the Wax Attack 2. Please read the safety instructions carefully and fully review the 3-step instructions before you begin. The Power-Pro Polisher is designed for compounding, polishing and waxing on clean paint surfaces using the supplied Mothers® products. Do not use this product for any other purpose.

## Important Safety Information

- ! Ensure power cord is disconnected before changing buffing pads.
- ! Only use the Wax Attack 2 polisher in a dry, dust-free environment.
- ! Beat the buffing pads out thoroughly before using (any particles or foreign bodies will scratch paintwork so the pads must be absolutely clean).
- ! Use both hands when necessary to firmly hold and guide your Wax Attack 2 polisher.
- ! Always switch off your Wax Attack 2 polisher before carrying it anywhere.
- ! When switching on and off, the polisher must be resting on the surface to be worked.
- ! Always keep the power cord over your shoulder to avoid unintended contact with paint.

## Operation – Switching On and Off

Place the Wax Attack 2 polisher on the surface to be worked. To switch on, push the button toward the 'I' marking on the switch. To switch off, push the button toward the 'O' marking on the switch.

## Removing the Buffing Pad

Be sure to place fingers between the loop material of the pad and the hook material of the machine.

*Do NOT pull directly on the foam to remove.*

## Before You Begin

It is important to start with a clean, dry and cool paint surface.

If the surface does not feel 100% smooth, use Mothers® California Gold® Clay Bar System (see back for more information). This will remove any surface contaminants and prepare the surface for step 1.

**Important: Do not apply any products directly to the paint surface.**

## 1 Professional Rubbing Compound: Paint Defect Removal

Dispense a circle pattern of Professional Rubbing Compound onto a clean buffing pad.




DISPENSE COMPOUND ONTO BUFFING PAD

Place machine on paint surface and massage product onto paint before switching on (this reduces product sling). Switch on and using light pressure, work an area about

2-3 square feet, overlapping the path by 50%, in at least 3 directions.

Reduce pressure as the product begins to dry. Do not buff dry.

Wipe surface clean with a soft, dry microfiber or terry cloth towel, and inspect the surface. Repeat this process until the surface is clear of defects.



OVERLAP PATH IN AT LEAST 3 DIRECTIONS

*NOTE: If you have scratches you can feel with your fingernail – you are NOT going to remove these.*

## VIDEO DEMO



Scan the code above with your smart phone to watch a short demonstration.

## 2 Professional Finishing Polish: Preparing Your Paint for Final Waxing

Dispense a circle pattern of Professional Finishing Polish onto a clean buffing pad.

Using light pressure, work an area approximately 2-3 square feet, once again overlapping the path by 50%, in at least three directions.



USE LIGHT PRESSURE, LET THE MACHINE DO THE WORK

Reduce pressure as the product begins to dry. Do not buff dry.

Wipe surface clean with a soft, dry microfiber or terry cloth towel.

*IMPORTANT: Do not move on to the next area until you are satisfied with the finish of each stage.*

## 3 California Gold® Synthetic Wax: Long Lasting Shine & Protection

Dispense a circle pattern of Mothers® California Gold® Synthetic Wax onto a clean buffing pad.



REMOVE HAZE WITH CLEAN, DRY TOWEL

Working with light pressure, spread wax evenly over a 2-3 square foot area. Buff area thoroughly while wet, then allow to dry to a haze.

Remove haze with a clean, dry microfiber or terry cloth towel. Turn towel frequently for best buffing action.

*NOTE: To avoid wax residue on trim, moldings and other non-painted plastic surfaces, first apply Mothers® Protectant or Back-to-Black® Trim & Plastic Restorer.*

## MAINTAIN YOUR SHOWROOM SHINE

Steps 1 and 2 remove defects and prepare your car's paint for final waxing. After this, we recommend doing step 3 often. Maintaining a protective coating of Mothers® California Gold® Synthetic Wax will reduce the need to use steps 1 and 2 in the future.

How long between waxing? If your vehicle is typically under cover, your wax may last a while. However, if it's left out in the elements, more frequent waxing may be required. On average, we recommend waxing every 8-12 weeks.

Go to [WaxForum.com](http://WaxForum.com) to check out our professional advice and videos.

**MAINTAIN YOUR MACHINE** – Clean your Wax Attack 2 with a damp cloth and dry thoroughly. Keep ventilation holes free of dust. Do not use solvents. The Wax Attack 2 polisher should always be stored in the original carry case.

**MAINTAIN YOUR PADS** – Wash the pads carefully by hand, using warm water and household detergent. Leave to air-dry, then store in the carry case or other dust-free environment.



If you drop a buffing pad on the ground, DO NOT USE - it will need to be washed before further use to avoid particle pickup, which can damage the paint surface!

