

FLOOR MATS INSTRUCTION MANUAL

Thank you for selecting floor mats from VIWIK. Your new floor mats are custom molded. VIWIK adopts the latest laser scanning technology to ensure that its floor mats accurately match the layout of the original car.

INSTALLATION INSTRUCTIONS

1. Remove the factory floor mats before installing your new floor mats. However, do not remove the factory-installed carpeting.
2. Move both front seats to their most rearward position. Once you have installed your mats, reposition the front seats so as to install the second seat floor mat.
3. Once you have installed the second seat floor mat, reposition the second seats.

CARE & NOTE

1. Due to long-distance transportation or packing compression, the floor mats may be slightly wrinkled. You can bend the product in the opposite direction several times to restore flatness.
2. The TPE material of the VIWIK floor liner is environmental-friendly, non-toxic, harmless, and easy to clean. When the floor liner needs cleaning, it only needs to be rinsed with a pressure washer and then left to dry.

SPECIFICATIONS

PRODUCT NAME: VIWIK Floor Mats

MATERIAL: TPE

WORKING TEMPERATURE: -58°F~167°F

WARRANTY: 1 year

DISCLAIMER & WARRANTY

WARRANTY PERIOD: 1 year from date of purchase.

VIWIK does not warrant its goods against any defect or damage caused by transportation, storage, improper installation and maintenance, internal or external hostile environments, misuse, abuse, negligence, accident, modification, tampering, the attachment of any unauthorized accessory, alteration to the goods, poor workmanship, or any other conditions whatsoever that cause a defect or failure of the product.

VIWIK's sole responsibility under this warranty shall be, at its option, to either repair or replace any goods which fail during the warranty period, provided that the buyer has promptly reported the said failure to VIWIK in writing, and complies with the provisions of this warranty.

For more information, please contact our customer support team.