

Datasheet (GL-BE3600)

Slate 7

Dual-band Wi-Fi 7 Travel Router



Slate 7 (GL-BE3600) is a dual-band Wi-Fi 7 portable travel router, designed to deliver internet speeds of up to 2882 Mbps (5GHz) and 688 Mbps (2.4GHz), with a maximum Wi-Fi speed of 3600 Mbps. Supporting both OpenVPN and WireGuard, Slate 7 ensures robust performance, capable of handling the heavy Wi-Fi usage of large households or small offices. Its compact and lightweight design ensures unparalleled portability, making it the perfect companion for travel, while its durable construction provides long-lasting performance wherever you go.

Highlights

BE3600 Wi-Fi 7 Technologies

Slate 7 utilizes the Wi-Fi 7 protocol, featuring enhanced OFDMA technology to minimize latency and improve network efficiency in multi-user, multi-device scenarios. Its 4K QAM technology increases transmission speed while further reducing latency. With MLO dual-band aggregation, it achieves combined speeds with a theoretical peak rate of up to 3.57Gbps, offering better anti-interference performance with two links.



Sleek Design & Touchscreen Interface

Slate 7 features a dark gray body with clean lines, rounded corners, and a textured matte finish, providing a comfortable, secure grip and a premium aesthetic. Its durable matte surface enhances both appearance and longevity, while the innovative touchscreen interface allows you to easily view and scan QR codes to connect to Wi-Fi, toggle the VPN on/off, and access other features— all at your fingertips for a seamless user experience.



High-Performance Hardware

Slate 7 is equipped with dual 2.5G Ethernet ports, each capable of delivering up to 2500 Mbps of broadband throughput. For storage, it features 512MB of flash memory alongside 1GB of high-performance RAM. The Type-C power port supports Power Delivery standards, with compatibility for 5V/3A, 9V/3A, and 12V/2.5A inputs. Slate 7 also includes a USB 3.0 port for external storage and a compact, lightweight adapter, optimizing portability without compromising performance.

VPN Security Encryption

Pre-installed with OpenVPN and WireGuard, Slate 7 supports over 30 VPN services. The device automatically encrypts all network traffic from devices within your network, ensuring robust security and privacy. Whether working remotely across borders or connecting to public Wi-Fi in hotels, cafés, or other shared environments, it guarantees comprehensive protection for your online activities.



Specifications

HARDWARE	
CPU	Qualcomm Quad-core @1.1GHz
Memory / Storage	1GB DDR4 / NAND Flash 512MB
Wi-Fi	2.4GHz: 802.11b/g/n/ax/be, 688Mbps 5GHz: 802.11a/n/ac/ax/be, 2882Mbps
External Antennas	2 x Antennas
Ethernet Speed	WAN Port: 1 x 2.5G Port (10/100/1000/2500Mbps) LAN Port: 1 x 2.5G Port (10/100/1000/2500Mbps)
Power Consumption	<18W (without USB)
Dimension / Weight	130 x 91 x 34mm (L*W*H) / 295g

SOFTWARE FEATURES	
Operating System	OpenWrt 23.05 (Kernel Version 5.4.213)
Network Mode	Routing, AP, Wireless Bridge, Wired Bridge
Ethernet Dialing Mode	DHCP, Static, PPPoE
Repeater Mode	Scans and Connects to SSID Connects to Hidden SSID
Wireless Configuration	Switching on and off wireless AP Modifying and hiding SSID Modifying encryption mode and password Channel modification Bandwidth modification Modifying transmission power Guest SSID

Display Flow Statistics (Cloud Platform Required)	Display product model, name, IP address, MAC address Current rate Flow statistics QoS settings
Client List	Show current connected clients Disable a client (no internet access)
Firewall Function	Port Forwarding, Open Port, DMZ
VPN	OpenVPN client & server WireGuard client & server Maximum OpenVPN Speed: 100Mbps Maximum WireGuard Speed: 540Mbps Policy routing
System Function	Restart Restore Factory Settings Change IP Address Range on LAN Side Change Time Zone MAC Address Clone Encrypted DNS DDNS Cloud Remote Management Remote Web Management Remote SSH Management Installing / Uninstalling Packages Drop-in Gateway Mode Multi-WAN

INTERFACE	
Ethernet Port	1 x 2.5G WAN, 1 x 2.5G LAN
USB Port	USB3.0 Type-A
Reset Button	Press (>3s, <8s) to Restores Network Settings to Device Initial State Long press (>=8s) to Restores Factory Settings
Power Port	Type-C interface Power Input: 5V/3A, 9V/3A, 12V/2.5A

CERTIFICATION

- CE
 - MIC
 - WEEE
 - UKCA
- FCC
 - RoHs
 - IC

ENVIRONMENT

Operating Temperature	0 ~ 40°C (32 ~ 104°F)
Storage Temperature	-20 ~ 70°C (-4 ~ 158°F)
Operating Humidity	5%~95%, Non-Condensing
Storage Humidity	5%~95%, Non-Condensing

PACKAGE CONTENTS

- 1 x Slate 7 (GL-BE3600) Router
- 1 x US Power Adapter
- 3 x Converters (EU, UK, and AU Plugs)
- 1 x Ethernet Cable
- 1 x Warranty Card
- 1 x User Manual

Note: The presented data rates are theoretical only, and actual values depend on network conditions.

CONTACT US

GL TECHNOLOGIES (HONG KONG) LIMITED
Unit 601, Building 5W, Hong Kong Science Park, Shatin, N.T., Hong Kong

WEBSITE www.gl-inet.com | **E-MAIL** sales@gl-inet.com