



Allied Flag™



# CONGRATULATIONS on your purchase of the best U.S. flag kit available today!

## The Highest Quality for the Best Price

Your flag's commercial-grade heavy duty 200 Denier solar colorfast nylon is guaranteed for 1 year against fading. Each Allied flag utilizes an industrial strength chain stitch for the highest levels of extended durability. Flag life expectancy is increased by 35% due to Allied's proprietary flag manufacturing process.

Allied's flag kit features new Never-Tangle Technology, which utilizes sealed weather-proof ball bearings. Never-Tangle Technology ensures your flag will always hang properly. Allied's premium flag kit utilizes stainless & polymer hardware attachments to prevent rusting and corrosion in all conditions.

Allied's premium flag kit features a heavy-duty 4-point universal bracket that allows for direct mounting to homes or flat surfaces. For curved or rounded pole mounting applications, the bracket features an available internal pass-through cinch design to accommodate any mounting requirements. This bracket features a 13 position 180-degree adjustable mount. The bracket is made of a forged casting design. It is oven-cured in a brilliant white powder coat to ensure a rust and oxidation-free install in any environment.



Allied's premium flag kit accurately displays the American flag to meet the flag etiquette standards as established by the United States Congress. Our flags are 100% made in the USA in Kansas City, Missouri with 100% U.S. sourced materials.

Complete kit includes everything needed for an easy, worry-free 2-minute installation. Our flag kits are backed by Allied's ironclad 100% hassle-free satisfaction guarantee.

**SEE REVERSE FOR INSTALLATION INSTRUCTIONS**

## Flag Kit Components



- (1) 3' pole
- (1) 2' pole
- Adjustable bracket
- Wall mounting screws
- (2) Mounting Rings
- 3x5' Embroidered Nylon Flag

### To Assemble Top and Bottom of Pole:

•Line up the threaded mounting section of the poles and screw together the connection until hand-tight. See figure 1-1.



### To Mount Flag on Pole:



• Unscrew the knurled tensioning screw completely from the ring. Slide the ring up the pole until it reaches the upper most flag grommet. Remove the Tensioning screw and pass it through the upper most grommet. Re-insert the tensioning screw into the tensioning ring. Tension should be no more than firmly finger-tight. *The metal hook at the top of the pole will not be used for this application. See Figures 1-2 and 1-3.*



•Repeat this step and slide the 2nd clear plastic mounting ring up to the bottom of the flag so that it meets with the lower left grommet of the flag. Insert the tensioning screw through the grommet while slightly stretching the flag. Note: Unscrewing the knurled tensioning screw may be necessary for the rings to pass freely over the pole.

### To Mount Flagpole to Building:

•Mount bracket to building with wood screws supplied. Screws may be utilized by directly attaching to building exterior, or plastic inserts may be required when mounting to masonry applications. In the event of a masonry installation, a mortar bit must be sourced prior to the holes being drilled. Mark holes prior to drilling, drill with masonry bit, insert plastic inserts, and secure the bracket with the supplied screws.

•Adjust bracket to desired angle and hand-tighten wing nut firmly to secure. Overtightening may damage the bracket.

•Insert pole into bracket.

•Hand-tighten set screw to secure pole.

**Have Questions?**

**Give us a call:**

1-888-932-3524

**Send us an e-mail:**

[info@usflagstore.com](mailto:info@usflagstore.com)