

# Campela™ Child seat

MODEL: CA0060

COLOUR:



## INFORMATION AND INSTALLATION:

This document contains information and guidelines that will be helpful to safely install and use the seat. The seat has EN 14344: 2004 certificate.

## WARNINGS AND GUIDELINES:

- 1) In order to maintain safety, the seat should be attached to a bike with a rack meeting EN14872: 2006 standard.
- 2) Minimum carrying capacity of the rack: 25 kg.
- 3) Luggage may be carried only at the front of the bike and it may not obscure the view while riding.
- 4) WARNING: Do not modify the child seat.
- 5) A child in the seat may affect the stability of the bike, the rider must therefore control the bike adjust riding.
- 6) WARNING: Never leave your bike parked with a child unattended in the seat.
- 7) WARNING: Never use the child seat if any part is damaged.
- 8) Avoid fast turns and rocks that pose a danger.
- 9) Avoid uneven surfaces and increased traffic.
- 10) WARNING: Do not attach additional luggage to the place where the child seat is located. Use a front rack or rear saddlebags to transport other loads. After installing the child seat, check that the bracket is correctly positioned in the fixture.

## MAINTENANCE:

Maintenance of the child seat is simple and does not require difficult procedures. Nevertheless, we advise you to follow these guidelines:

1. Regularly check the installation of the child seat.
2. Clean with a cloth and soapy water. Do not use products causing abrasion or corrosion.
3. Make sure all belts are working properly.
4. Regularly, two times, check the overall condition of the child seat.
5. The pillow may be cleaned with soapy water and left to dry flat.

## INSTALLATION:

**The bicycle child seat may be attached to the bicycle frame or the rack - fig. 1-2.**

**Installation of the child seat to the bicycle frame - fig. 1:**

1. The bracket has two screws, two metal washers and adapters. Connect all of these elements together at the proper height of the bicycle frame. If the diameter of the frame is too small, use the appropriate plastic adapter - two halves. They must be inserted between the handle and the frame (fig. 3). 28-40mm.

2. Then connect the seat to the metal mast using suitable: metal and plastic washers, screws and nuts (fig. 4).
3. In order to install the seat, slide the metal mast to the mounting bracket so that the latch is aligned respectively with the tube. After connecting the metal mast and the buckle, push the latch in the "closed" direction. Make sure that the bracket is properly locked (fig. 5)
4. Adjust the desired height of the child seat: the average of 1.5-2 cm above the rack (fig. 6).

#### **Installation of the child seat on the rack (min. carrying capacity of the rack: 25 kg) - fig. 2:**

1. In order to install the seat on the rack, the following is needed: two metal washers, 4 screws.
2. Lay the child seat on the rack; then put 4 M6 bolts through the holes in the child seat (fig. 7).
3. Tighten two metal washers with the screws on the underside of the child seat (fig. 8).
4. Connect the child seat with the seat post (fig. 9) by using the belt. After installing the seat, place a child in it, in order to adjust the size and height of the seat belts and adjust the footrests. The length of the belt may be adjusted according to fig. 10. In order to adjust the leg supports, use the corresponding holes - fig. 11. Be careful that the child's feet are not squeezed too much with the fastening belts.
5. If you use a spring under the rear rack, use a plastic protector on your toes to avoid injury. The plastic protector is provided in the box. (fig. 12).

#### **SAFETY GUIDANCE:**

- 1) Regularly check that all screws are tightened.
- 2) Regularly check the bike condition.
- 3) Minimum age of the rider: 16 years old.
- 4) The child seat allows to carry a child weighing not more than 22 kg, which can already sit, and is not older than 7 years old.
- 5) The child seat may be attached to the bicycle frame with a diameter of: 28-34 mm.
- 6) When attaching the child seat to the rack, the distance between the centre of gravity of the seat and the axis of the rear wheel may reach up to 10 cm (fig. 2).
- 7) Protect a child in the child seat with the belts, and put on a protective helmet on his/her head.
- 8) Wear belts on the child's feet, so as not to be injured by trapping his/her feet between the spokes.
- 9) Never carry more than one child at the same time.

